

Stainless Steel Full IP66/IP69K

FIP-10W

10.1" IP proof monitor



Specification

IP66 I/O Interface:

- VGA : 1 x VGA (M12 connector)
- DVI : N/A
- HDMI : 1 x HDMI (IP66 HDMI connector)
- Video : N/A
- USB : 1 x USB for touch (M12 connector)
- Power Input : 1 x 12V DC input (M12 connector)

Power Specification:

- Power Adapter : 1 x AC/DC Power adapter
- Consumption : 15W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : 1 x 1.5m power cord (Type provided by region)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -30 deg. C to 70 deg. C
- Humidity : 30~90% non-condensing
- IP Grade : Full-IP66/IP69K

Panel Specification :

- Size/ Type : 10.1" LCD
- Active Area (mm) : 200.416 (H) x 129.15 (V)
- Pixel Pitch (mm) : 0.2125(H) x 0.21525(V)
- Resolution : 1280 x 800 @ 60Hz, 75Hz
- Contrast Ratio : 800 : 1 (typ.)
- Max. Colors : 16.7M Colors
- Brightness : 350 nits (cd/m²)
- Viewing Angle : -85~ 85 (H); -85~ 85 (V)
- Touch : P-cap multi-touch (USB)

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

System Information :

- Hardness : Vandal Proof with optical bonding
- Housing : Stainless Steel SUS 304
- Connector : Full-IP66 Circular connectors
- Mounting : 75x 75 VESA Mount. Panel mount for optional

Order Information :

- Optical Bonding : Optical Bonding (for optional)
- Vandal proof : 6-10 mm vandal proof touch screen (optional)
- Power Input : 9~36V DC or 100~240V AC Power Input (optional)

Drawings:

