

Full IP65 Stainless Steel Monitor

FIP-42W

43" Stainless Steel Full-IP65 Display



Features:

- 43" LED Backlight
- Full-HD 1080p Input
- Anti-Corrosion Stainless Steel 316
- Deactivated Surface Coating
- Full-IP65 Protection

Specification

IP65 Input / Output :

- | | |
|---------------|--------------------------------|
| • VGA | : 1 x VGA (IP65 connectors) |
| • DVI | : 1 x DVI-D (IP65 connectors) |
| • HDMI | : 1 x HDMI (for optional) |
| • Video | : NA |
| • USB | : 1 x USB for touch (optional) |
| • Power Input | : 1 x AC input |

System Specification:

- | | |
|--------------------|---|
| • Housing Material | : Stainless Steel with deactivated coating for anti-corrosion |
| • Dimensions | : 104.1 x 63.3 x 8 (WxHxD) (cm) |
| • Weight | : 38KG |
| • OSD Control | : Auto video input detected |
| • Speakers | : 2 x 2W speakers integrated (Optional) |
| • Protective Glass | : 1 x 3mm thickness protective glass |
| • Mounting Type | : VESA mount and 3x hangers |

Power Specification:

- | | |
|-----------------|-------------------------------------|
| • Power Input | : 90~260V AC Input (IP65 Connector) |
| • Consumption | : 80 W typical, normal operation |
| • Management | : VESA DPMS compliant |
| • Power Cord | : 1x 1.8m AC Power Code (EU type) |
| • Power Adapter | : No Power Adapter |

Panel Specification :

- | | |
|--------------------|--------------------------------------|
| • Size/ Type | : 43" LCD (LED backlight) |
| • Active Area (mm) | : 940.89 (H) x 529.25 (V) |
| • Pixel Pitch (mm) | : 0.49 (H)x 0.49 (V) |
| • Resolution | : 1920 x 1080 @ 60Hz |
| • Contrast Ratio | : 3,000 : 1 (typ.) |
| • Max. Colors | : 16.7M colors |
| • Brightness | : 400 nits (cd/m ²) |
| • Viewing Angle | : -89 ~ 89 (H); -89 ~ 89 (V) |
| • Glass | : AR anti-shattered protective glass |

Environment Tolerance:

- | | |
|-------------------------|-------------------------------|
| • Operating Temperature | : 0 deg. C to 50 deg. C |
| • Storage Temperature | : -20 deg. C to 70 deg. C |
| • Operating Humidity | : 10% to 95% (Non Condensing) |
| • IP65 | : Full- IP65 |

Order Options :

- | | |
|-------------------|---|
| • Touch Screen | : P-cap multi touch screen (optional) |
| • High Brightness | : 1,000 nits high brightness (optional) |

Drawings

