

LCD Touch Monitor

LCH-43W-CP

43" LCD (LED backlight) Monitor for Multiple Applications



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-I input
- HDMI : 1 x HDMI input (Optional)
- DP : 1 x Display Port (optional)
- USB : 1 x USB port for touch(optional)
- Power Input : 1 x AC input

Power Specification:

- Power Adapter : N/A
- Consumption : 120 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : Provided by region

Environment Tolerance:

- Operating Temperature : 0 deg. C to 45 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Water/Dust proof : Front IP54
- Humidity : 30~70% RH (Non-condensing)

Panel Specification :

- Size/ Type : 43" LCD (LED backlight)
- Active Area (mm) : 940.89 (H) x 529.25 (V)
- Pixel Pitch (mm) : 0.49 (H)x 0.49 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 3,000 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 400 nits (cd/m²)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)
- Touch Screen : P-cap multi-touch (USB)

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :

- Touch : IR Touch Screen
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1,000 nits (optional)

Drawings

