

All Flat Series- Zero Bezel

LFS-15W

15.6" (16:9) Wide LCD Touch Monitor



Features:

- LED Backlight Display
- -5~55°C Wide Range Operating Temperature
- Projected Capacitive Multi Touch Screen
- Front-IP65 Protection

Specification

Input / Output :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-I input (optional)
- HDMI : 1 x HDMI input (optional)
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch screen
- Power Input : 1 x DC input w/external power adapter

Power Specification:

- Power Adapter : 1 x AC/DC Power Adapter
- Consumption : 16 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : Provided by region

Environment Tolerance:

- Operating Temperature : -15 deg. C to 60 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP65 : Front IP65
- Vibration : 5 Hz ~ 500 Hz/ 1 Grms/ 3 Axis
- Shock : 15G, 11ms duration

Panel Specification :

- Size/ Type : 15.6" (16:9) LED backlight
- Active Area (mm) : 344 (H) x 194 (V)
- Pixel Pitch (mm) : 0.3 (H)x0.3 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 500 : 1 (typ.)
- Max. Colors : 262K colors(6 bits)
- Brightness : 400 nits (cd/m²)
- Viewing Angle : -80 ~ 80 (H); -70 ~ 70 (V)
- Touch Screen : P-cap multi touch screen

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Options :

- Touch Screen (Optional) : 5-Wire resistive touch screen
- High Brightness (Optional) : 1,000 nits high brightness
- VESA Mount Kit (Optional) : 1 x VESA or Pipe Mount kit

Drawings

