

LCD Monitor

LOF-19W

19" (16:10) LCD Open Frame Touch Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D (optional)
- HDMI : NA
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch
- Power Input : 1 x 9~36V DC input (Terminal block)

Power Specification:

- Power Adapter : N/A
- Consumption : 23W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : N/A

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C

Panel Specification :

- Size/ Type : 19" (16:9) LCD (LED backlight)
- Active Area (mm) : 408.24 (H) x 255.15 (V)
- Pixel Pitch (mm) : 0.2835 (H) x 0.2835 (V)
- Resolution : 1440 x 900 @ 60Hz, 75Hz
- Contrast Ratio : 1000 : 1 (typ.)
- Max. Colors : 16.7M (6 bits + FRC)
- Brightness : 250 nits (cd/m²)
- Viewing Angle : -85 ~ 85 (H); -80 ~ 80(V)
- Touch : 5-wire resistive touch screen(optional)

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :

- Touch : 5-wire touch screen (optional)
- Glass : AR glass protection (optional)
- Speaker : 2W Speaker x2 (optional)

Drawings

