

LCD Touch Display

LOF-32W

32" Open Frame LCD Touch Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI
- Video : S-Video, Composite (optional)
- COM : 1 x RS232 for touch (optional)
- Power Input : 1 x DC input (terminal block)

Power Specification:

- Power Input : 9~36V DC Input (Isolated)
- Consumption : 65 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : N/A

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C

Panel Specification :

- Size/ Type : 32" LCD (LED backlight)
- Active Area (mm) : 698.4 (H) x 392.85 (V)
- Pixel Pitch (mm) : 0.3638 (H)x 0.3638 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 4000 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 350 nits (cd/m²)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)
- Touch : P-cap multi- touch

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :

- Touch : SAW (Optional)
- Glass : AR glass protection (optional)
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1000 nits (optional)

Drawings

