

Stainless Steel Panel PC

PST-22WJ

21.5" Stainless Steel PPC (Intel Baytrail Platform)



Features:

- Ultra Low Power Baytrail Processor J1900 2.0GHz
- -5~55°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Housing Design
- High Brightness: 1,000 nits for optional
- Curve, elegant edge design

Specification

System:

- CPU : Intel Baytrail-M Celeron J1900 2.0GHz
- Chipset : Intel SoC integrated
- Memory : DDR3 1066/1333MHz SO-DIMM 4GB
- Storage : 1x mSATA 64GB
- Ethernet : Dual Realtek RTL8111G GbE Controller
- BIOS : AMI 16Mbit Flash
- Audio Codec : Realtek ALC269 HD Audio Codec
- Expansions : 1 x Mini PCIe slot (for Wireless card)
- Cooling System : Fanless design
- WiFi : 802.11 b/g/n 2x2 Dual Band (optional)
- Mounting Type : 200 x 100 VESA holes

Input / Output :

- Serial Ports : 3 x RS232
- USB Ports : 4 x USB2.0
- Ethernet : 2 x RJ45 GbE LAN
- Power : AC 110~240V, Universal, $\pm 10\%$
- Video : 1 x VGA Output, 1 x HDMI Output
- PS/2 : 1 x PS/2 for keyboard/mouse
- Audio : 1 x Line Out, 1 x Mic In

Panel Specification :

- Size/ Type : 21.5" TFT
- Resolution : 1920 x 1080
- Brightness : 250 cd/m²(typ.)
- Contrast Ratio : 1000 : 1 (typ.)
- Viewing Angle : 170 (H) ; 160 (V)
- Max. Colors : 16.7M
- Touch : 5-wire resistive touch screen

Environment Tolerance:

- Operating Temperature : -5 deg. C to 55 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- Storage Temperature : -30 deg. C to 70 deg. C

Order Options :

- High Brightness : 1000 cd/m² (Optional)
- Power Input : 9~36V DC Input (Optional)
- Custom I/O port : By request

Power Specification :

- Power Adapter : No power adapter
- Power Consumption : 40W (typ.)

Drawings:

