

Slim Type Stainless Full-IP65 LCD

FIP-17R

17" Full-IP65 Stainless Steel LCD



Specification

System:

•Housing	: Anti-corrosion stainless steel with deactivated coating
•Color	: Sliver Color (Others by request)
•OSD Input	: 5-key OSD buttons
•OSD Function	: Contrast, Color, Position, Auto adjustment, Factory Settings
•Mounting	: 100 x100 VESA Mount

IP66 I/O connectors :

•Video Input	: VGA (or DVI)
•USB	: USB for touch screen
•Power	: AC 110~240V, Universal, ±10%

Power Specification :

•Power Adapter	: No power adapter
•Power Consumption	: 40W (typ.)

Features:

- -20~60°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Housing Design
- High Brightness: 1,000 nits for optional
- Slim & Curve Edge

Panel Specification :

•Size/ Type	: 17" TFT LCD
•Resolution	: 1280 x 1024
•Brightness	: 400 (cd/m ²)
•Contract Ratio	: 1000 : 1 (typ.)
•Viewing Angle	: -85~85 (H) ; -80~80 (V)
• Max. Colors	: 16.2M (6bits+ FRC)
• Touch	: 5-wire resistive touch Or P-cap touch screen (default)

Environment Tolerance:

•Net Weight	: 8 KG (Identity)
•Operating Temp.	: -20 deg. C to 60 deg. C
•Storage Temp.	: -40 deg. C to 80 deg. C
•Operating Humidity	: 10% to 95% (Non Condensing)
•IP65	: Front IP65
•Vibration	: MIL-STD-810G Method 514.6C-3
•Shock	: MIL-STD-810G Method 516.6

Order Options :

•High Brightness	: 1000 cd/m ² (Optional)
•Touch Screen	: 5-wire resistive touch (Optional)
•Power Input	: 9~36V DC Input (Optional)
•Custom I/O port	: By request

Drawings:

