

FIP-32WHS

32" Stainless Steel Full-IP67 Panel PC



- Features:**
- Intel® Haswell Core i5 5250U
 - Full IP67/ IP69K
 - 0 ~ 50°C Operating Temperature
 - Anti-corrosion SUS316 stainless steel

Specification

System:

• CPU	: Intel® 5 th Gen. Broadwell Core i5 5250U 2.2 GHz (Max. up to 2.7GHz)
• Memory	: DDR3 So-DIMM 4GB (max. 8GB)
• Storage	: SATAII HDD 500GB or mSATA SSD 64GB
• Graphic	: Integrated Intel® HD Graphics
• Ethernet	: Intel® Ethernet Controller I211-AT + Intel® Gigabit Ethernet PHY I218-LM
• BIOS	: AMI 16 MB Flash
• Wireless	: WiFi 802.11 b/g/n, BT 4.0 (For optional)
• Mounting	: 200x100, 400x100 VESA mounting thread
• Housing	: Stainless steel SUS316
• Touch	: P-cap multi-touch (for optional)

Input / Output :

• Serial Ports	: 2 x RS232 (IP65)
• USB Ports	: 2 x USB 2.0 (IP65)
• Ethernet	: 2 x RJ45 GbE LAN (IP65)
• Power	: AC 110~240V, Universal, ±10% (IP65)

Panel Specification :

• Size/ Type	: 32" LCD (LED backlight)
• Active Area (mm)	: 698.4 (H) x 392.85 (V)
• Pixel Pitch (mm)	: 0.3638 (H)x 0.3638 (V)
• Resolution	: 1920 x 1080 @ 60Hz
• Contrast Ratio	: 3000 : 1 (typ.)
• Max. Colors	: 16.7M colors
• Brightness	: 500 nits (cd/m ²)
• Viewing Angle	: -89 ~ 89 (H); -89 ~ 89 (V)
• Glass	: AR protective glass

Environment Tolerance:

• Operating Temperature	: 0 deg. C to 50 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP Grade	: Full- IP67, NEMA6

Order Options :

• OS	: Windows 7, Win10 IOT
• High Brightness	: 1,000 cd/m ² (Optional)
• Platform	: Intel® Baytrail / Apollolake platform (Optional)
• Custom I/O	: By request

Power Specification :

• Power Adapter	: N/A
• Power Consumption	: 110W (typ.)

Drawings

