

LCD Display

LCH-11W

11.6" (16: 9) LCD Monitor



Specification

Input / Output :

- | | |
|-------------------|-----------------------------|
| • VGA | : 1 x VGA D-sub 15pin input |
| • DVI | : 1 x DVI-D Input |
| • HDMI | : 1 x HDMI Input |
| • USB | : N/A |
| • Power Connector | : 1 x 3-pin terminal block |

Power Specification:

- | | |
|-----------------|---|
| • Power Input | : DC 12V Input |
| • Consumption | : 24 W typical, normal operation |
| • Power Adapter | : 1 x AC/DC Power adapter |
| • Power Cord | : 1 x 1.5m power cord (type provided by region) |

Environment Tolerance:

- | | |
|-------------------------|---------------------------|
| • Operating Temperature | : 0 deg. C to 55 deg. C |
| • Storage Temperature | : -20 deg. C to 70 deg. C |

Panel Specification :

- | | |
|------------------|----------------------------------|
| • Size/ Type | : 11.6" (16:9) |
| • Resolution | : 1920 x 1080 @60Hz |
| • Brightness | : 350 (cd/m ²) |
| • Contract Ratio | : 800 : 1 (typ.) |
| • Viewing Angle | : -89~89 (H) ; -89~89(V) |
| • Max. Colors | : 262K colors (8 bits/color) |
| • Glass | : AR protective glass (optional) |

Specification:

- | | |
|--------------------|--------------------------|
| • Housing material | : Heavy duty steel sheet |
| • Mounting | : 75x 75 VESA Mount |
| • Dimensions | : |
| • Weight | : 3 KG |

OSD :

- | | |
|----------------|--|
| • OSD Input | : 5-key OSD buttons |
| • OSD Function | : Contrast, Color, Position, Auto-adjustment, Factory Settings |

Drawings

