

LCD Touch Display

LOF-15R

15" LCD Open Frame Touch Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D (optional)
- HDMI : NA
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch
- Power Input : 1 x 12V DC input

Power Specification:

- Power Adapter : AC to 12V DC output adapter
- Consumption : 32W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : Provided by region

Environment Tolerance:

- Operating Temperature : -10 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C

Panel Specification :

- Size/ Type : 15" LCD (LED backlight)
- Active Area (mm) : 304.1 (H) x 228.1 (V)
- Pixel Pitch (mm) : 0.297 (H) x 0.297 (V)
- Resolution : 1024 x 768 @ 60Hz, 75Hz
- Contrast Ratio : 500 : 1 (typ.)
- Max. Colors : 16.2M
- Brightness : 250 nits (cd/m²)
- Viewing Angle : -70 ~ 70 (H); -60 ~ 60(V)
- Touch Screen : 5-wire resistive touch , either or P-cap multi -touch screen

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Option :

- Glass : AR glass protection (optional)
- Power Input : 9~36V wide range DC Input
- High Brightness : 1000 nits (optional)

Drawings

