

# Industrial LCD Touch Display

## LPM-32W-CP

32" Wide Screen / Front IP65 / Panel Mount Monitor



### Specification

#### Input Interface :

- VGA : 1 x VGA
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (optional)
- DP : 1 x DP (optional)
- USB : 1 x USB for touch (optional)
- Power Input : 1 x AC input

#### Keypad :

- OSD buttons : 5-key OSD buttons

#### Power Specification:

- Power Input : 100~ 240V AC Input
- Consumption : 80 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : 1 x Power Cord
- Power Adapter : N/A

#### Panel Specification :

- Size/ Type : 32" LCD (LED backlight)
- Active Area (mm) : 698.4(H) x 392.9 (V)
- Pixel Pitch (mm) : 0.6375(H)x0.6375(V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 3000 : 1 (typ.)
- Max. Colors : 16.7M (8 bits + FRC)
- Brightness : 400 nits (cd/m<sup>2</sup>)  
(1,000 nits for optional)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)
- Touch Screen : P-cap multi touch (optional)

#### Environment Tolerance:

- Operating Temperature : 0 deg. C to 45 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- IP Level : Front IP65

#### Accessory:

- Cable : 1 x 1.5m VGA cable  
1 x 1.5m DVI cable  
1 x 1.5m Power cable
- Driver CD : 1 x Driver CD for touch screen  
(Resistive touch)

#### Order Options :

- Touch : P-cap touch screen (USB)
- Power Input : 24V DC Input

### Drawings

