

Rack Mount Monitor

LRK-17R

17" Rack Mount Monitors



Features:

- Rack mount Housing Design
- Either 5-wire resistive or P-cap touch screen

Specification

System Specification:

- OSD : Front 5-key OSD Controller
- Housing : Front Alu. front bezel
- Mounting : 19" Rack Mount (with or without front handles)
- IP Proof : Front IP65

Input / Output :

- Power : 12V DC IN (Terminal Block)
- VGA : 1 x VGA (D-sub 15pin)
- USB : 1 x USB for touch screen

Environment Compliance:

- Operating Temperature : -10 deg. C to 55 deg. C
- Operating Humidity : 10% to 90% (Non-condensing)
- Storage Temperature : -30 deg. C to 70 deg. C
- IP Grade : Front IP65

Panel Specification :

- Size/ Type : 17" TFT LCD
- Resolution : 1280 x 1024
- Brightness : 300 (cd/m²)
- Contract Ratio : 1000 : 1 (typ.)
- Viewing Angle : -85~85 (H) ; -80~80 (V)
- Max. Colors : 16.2M (6bits+ FRC)
- Glass : 5-wire resistive or P-cap multi-touch

Power Specification :

- Power Adapter : AC/DC power adapter
- Power Consumption : 20W (typ.)

Order Option:

- High Brightness : 1,000 nits high brightness sunlight readable
- Color : Custom Color for optional
- Wide range power : 9~36V wide range DC Input for optional
- Connectors : MIL. D38999 III connectors for optional

Drawings:

